

Vacuum Glass Lifter


serie VB8+4 RCMBM

1200 kg



Technical specification

Application	Glass panels
Lifting capacity	1200 kg in 12 pads configuration 800 kg in 8 pads configuration
Suction pads	No. 12 round suction pads diameter 310 mm (8 fixed pads + 4 pads on removable extension arms) Lipped pads with safety ring
Load movement	Continuous 360 degree manual rotation 90 degree manual tilt
Pad spread	8 pads configuration mm 1420 x 970 12 pads configuration mm 2145 x 1488
Operating system	DC vacuum pump powered from on-board batteries high capacity re-chargeable batteries battery status indicator economizer for reduction of the energy consumption
Vacuum system	2 independent vacuum circuits, each vacuum circuit with vacuum reserve and non return valve
Weight of lifter	100 kg
Structural depth	mm 250
Control	Manual on off valve on the lifter's frame Release of the load by dual action security command Remote control as optional
Standard features	Audible and visual low vacuum warning devices Vacuum gauge for each vacuum circuit Battery charger 240 Volt Vacuum filter Multi position hook connection Lowered suspension for installing of transom window



- **battery operating system**
- **modular frame**

- 8+4 suction pads
- Manual continues 360° rotation
- Manual 90° tilt
- Lifting capacity 1200 kg
- Safety devices

✓ Dual vacuum circuit built to EN13155 standard

